

EPG SERVER **EPG VS**

ISDB-T INTERNATIONAL STANDARD

► **Adaptable to different
environments and needs**

► **Own and scalable
development**

USER INTERFACE

INSTANCE / NETWORK

AVAILABLE TRANSPORTS BASED ON NETWORK

AVAILABLE SERVICES BASED ON TRANSPORT

CURRENT EVENTS BASED ON SERVICE

DATA ENTRY

EPG SERVER

ELECTRONIC PROGRAM GUIDE

TV VIEWER

TELEVISION CHANNEL

MAIN FEATURES

- EPG and SI (Service Information) Tables generation for ISDB-T International
- Transmission and control of Ginga applications via Web Scheduler
- System to update the software of receivers via OAD (On-Air Download)
- Closed Caption for the hearing impaired
- ASI and IP outputs: TCP, UDP, Unicast and Multicast
- Configurable output bit rate
- Automatic reading of scheduled program data with configurable times
- Critical error message via email
- Manual loading of the programming guide
- Configurable number of days
- User-friendly and simple user interface

- Tables and Descriptors Generator based on Service Information in ISDB-T International standards.
- It creates and generates static and dynamic tables in compliance with specifications ARIB STD-B10, TR-B14 and ABNT NBR 15603, NBR 15608.
- It generates a TS on an ASI or IP output interface, through pre-configurable PIDs mapping for each table and transport.
- It generates the NIT (Network Information Table), BIT (Broadcaster Information Table), SDT (Service Description Table), EIT (Event Information Table), TDT (Time & Date Table), TOT (Time Offset Table), AIT (Application Information Table), and SDTT (Software Download Trigger Table), with their respective descriptors.
- Generation of H-EIT (Fixed Receiver), M-EIT (Mobile Receiver), and L-EIT (Portable Receiver), P/F (Present / Following) tables, as well as S (Schedule), both for actual transport (Actual), and for other transports (Other).
- Possibility of configuring which tables to generate, as well as controlling the repetition rate of each one independently, thus accomplishing a better bandwidth use.
- Flexible configuration of the range of days in which the EPG is generated, starting at 1 to 7 days and, optionally, up to a maximum of 32 days.
- Possibility of configuring the maximum number of characters to be included in the text fields of EIT tables in a dynamic way, thus enabling the adjustment of the generated data volume, and also for adapting it to the memory requirements of receiving devices.
- Import EPG of scheduled program data as XML files and other formats (optional) through multiple access devices (e.g.: LAN, FTP, DVD, USB, etc.).
- Configuration of programming import filters, which can detect overlappings and discontinuities of the events imported for each service.
- Scheduling via Web, Generation and Transmit control of Ginga Applications and Software updates over the air (OAD - On-Air Download), through DSM-CC carousels according to specifications ABNT NBR 15606, NBR 15608, ARIB STD-B21, STD-B23, TR-B14, ISO/IEC 13818-6.
- Closed Caption generation for the hearing impaired from the local keyboard (USB), Closed Caption Client Remote (IP), or a Closed Caption Decoder (RS-232/IP) for the case of signals existing CC video embedded, according to specifications ABNT NBR 15606, NBR 15608, ARIB STD-B24, TR-B14.
- Client/Server Architecture, with a centralized Database, and optionally, one or multiple remote editing terminals.
- 1:1 Redundant server option with automatic switching and error messages via email.
- User management and user action log.
- Dynamic and intuitive graphic interface.
- Scalable and configurable.
- Support virtualized environments.
- This system is part of the product offer of VideoSwitch transmission in the ISDB-T International standard, such as the Encoder 'ECD-3000' and the 'DMUX-3100/510' multiplexers.

EPG SERVER	
ISDB-T INTERNATIONAL	
CHARACTERISTICS	Compatible with ISDB-T International EPG, SI, Ginga, Software Update and Closed Caption Standards (ARIB, ABNT, ISO/IEC) Generate EIT-Present/Following and EIT-Schedule Tables Additionally can generate NIT, BIT, SDT, TDT, TOT, AIT, SDTT Tables, and DSM-CC carousels for Ginga and Software Updates (OAD) applications
INPUTS	XML files coming from the network (LAN, FTP) or from external devices (DVD, USB)
OUTPUTS	Interface: DVB-ASI (dual) / IP (UDP/TCP) Connectors: BNC, 75 Ohms / RJ45 Bit Rate Max.: 100 Mbps (UDP) / 20 Mbps (TCP)
PLATFORM PROPOSED SERVER	Dell Power Edge Server® (1U rack) or similar IP-ASI Converter for bitrate management, status monitoring and automatic redundancy

EPG
SERVER



© Dell is a registered trademark of Dell Inc.

